SAFE WORK METHOD STATEMENT (SWMS)

Business name

Document: SWMS-001 Rev 1
Prepared: 9 Nov 2026
Review by: 9 Dec 2026
Highest risk after controls: Medium

1. BUSINESS AND JOB DETAILS

Job	Gyprock patching and repairs	**Start date**	9 Nov 2026
Working hours	7:00 am to 3:30 pm	**Trade**	Plastering and gyprock

2. HIGH RISK CONSTRUCTION WORK COVERED BY THIS SWMS

	Risk of a person falling more than 2 metres		Work on or near chemical, fuel or refrigerant lines
	Work on a telecommunication tower		Work on or near energised electrical installations or services
	Demolition of an element of a structure that is load-bearing or related to its physical integrity		Work in an area that may have a contaminated or flammable atmosphere
	Likely to involve disturbing asbestos		Work involving tilt-up or precast concrete elements
	Structural alterations or repairs that require temporary support to prevent collapse		Work on, in or next to a road, railway, shipping lane or other traffic corridor in use by traffic other than pedestrians
	Work in or near a confined space		Work in an area with movement of powered mobile plant
	Work in or near a shaft or trench with an excavated depth greater than 1.5 metres		Work in an area with artificial extremes of temperature
	Work in or near a tunnel		Work in or near water or other liquid that involves a risk of drowning
	Use of explosives		Diving work
	Work on or near pressurised gas distribution mains or piping		

3. JOB STEPS, HAZARDS AND CONTROLS

#	Job step	Hazards	Risk before	Controls	Risk after	Responsible
1	Check for asbestos in older linings before cutting	Disturbing asbestos Rules: WHS Regulations, Chapter 8 (Asbestos)	**Extreme Possible / Catastrophic**	1.1 Before work, check the asbestos register (workplaces built before 2004). For homes, or if there is no register, have a competent person identify asbestos or assume it is present. [Eliminate] 1.2 Seal off the work area and keep everyone else out. [Isolate] 1.3 If asbestos must be disturbed, keep it wet, use hand tools not power tools, and clean up with an H-class vacuum. [Engineering] 1.4 Friable asbestos (Class A) and more than 10 square metres of non-friable asbestos (Class B) must be removed by a licensed removalist. [Administrative]	**Medium Rare / Catastrophic**	Site supervisor

#	Job step	Hazards	Risk before	Controls	Risk after	Responsible
				1.5 Stop work straight away if you find suspect asbestos. Do not touch it and tell your supervisor. [Administrative] 1.6 Wear a fitted P2 (or better) respirator and disposable coveralls. [PPE]		
2	Check for cables and pipes behind the wall	Electric shock from live wiring Rules: WHS Regulation 2011, Part 4.7 General electrical safety	**Extreme Possible / Catastrophic**	2.1 Isolate the power before any work. Do not do live work except in the limited cases the WHS Regulations allow (r.157; in Qld, the Electrical Safety Regulation 2013). [Eliminate] 2.2 Lock out and tag the isolation point with your own personal lock and danger tag. [Isolate] 2.3 Test before you touch: prove dead at the point of work with a voltage tester, proving the tester on a known live source before and after (AS/NZS 4836). [Engineering] 2.4 Only licensed electricians do electrical work. [Administrative] 2.5 Check for back feeds from solar, batteries and generators that can keep a circuit live after the main switch is off. [Administrative] 2.6 If live work cannot be avoided, use a permit, a safety observer and insulated tools. [Administrative] 2.7 Wear insulated gloves, arc-rated clothing and a face shield when testing or working near live parts. [PPE]	**Medium Rare / Catastrophic**	Site supervisor
3	Cut out damage and fit a patch	Cuts from sharp edges General dust	**Medium Likely / Minor**	3.1 Deburr or cover sharp edges, and fit edge protectors on exposed sheet metal. [Engineering] 3.2 Use knives with retractable or self-retracting blades. [Engineering] 3.3 Cut away from your body and keep your other hand clear. [Administrative] 3.4 Put used blades in a blade bin or sharps container. [Administrative] 3.5 Use two people to handle large sheets of metal or glass. [Administrative] 3.6 Wear cut-resistant gloves and long sleeves. [PPE] 3.7 Use low-dust products, such as dust-reduced or pre-mixed compounds. [Substitute] 3.8 Seal off the work area with plastic sheeting in occupied buildings. [Isolate] 3.9 Use tools with dust extraction and a vacuum for clean up. [Engineering] 3.10 Lightly mist the area with water to keep dust down, away from anything electrical. [Engineering] 3.11 Never dry sweep or blow dust off with compressed air. [Administrative] 3.12 Wear a dust mask and safety glasses. [PPE]	**Low Unlikely / Minor**	Site supervisor
4	Set, sand and finish	General dust Falling from a ladder Rules: WHS Regulation 2011, Part 4.4 Falls	**High Possible / Major**	4.1 General dust: see step 3 for the full controls [Administrative] 4.2 Use a platform ladder, mobile scaffold or EWP for longer jobs instead of a straight ladder. [Substitute] 4.3 Use industrial-rated ladders (AS/NZS 1892, 120 kg or more) in good condition. Remove any damaged ladder from site. [Engineering] 4.4 Set extension ladders at a 4 to 1 angle on firm, level ground, tied or footed, and reaching 1 metre above the landing. [Engineering]	**Medium Unlikely / Major**	Site supervisor

#	Job step	Hazards	Risk before	Controls	Risk after	Responsible
				4.5 Use ladders only for short, light work. Do not carry heavy or awkward loads up a ladder. [Administrative] 4.6 Keep three points of contact and your belt buckle between the stiles. Do not overreach. [Administrative] 4.7 Do not stand on the top three rungs of an extension ladder or the top step of a stepladder. [Administrative] 4.8 Check the ladder before each use: feet, rungs, stiles and locks. [Administrative] 4.9 Wear non-slip safety boots with clean soles. [PPE]		
5	Clean up	Poor housekeeping and waste	**Medium Likely / Minor**	5.1 Order materials to size and send packaging back where you can. [Eliminate] 5.2 Put skip bins and waste chutes close to the work. [Engineering] 5.3 Clean as you go, and do a full clean up at the end of each day. [Administrative] 5.4 Keep exits, stairs and walkways clear at all times. [Administrative] 5.5 Stack materials neatly on level ground, away from edges. [Administrative] 5.6 Wear gloves when handling waste. [PPE]	**Low Unlikely / Minor**	Site supervisor

Risk key: risk = likelihood x consequence on a 5 x 5 matrix. Low, Medium, High, Extreme. Work must not start while the risk after controls is high or above. Controls are listed in order of the hierarchy of control: Eliminate, Substitute, Isolate, Engineering, Administrative, PPE.

4. PPE AND PERMITS

Required PPE	Permits and plans
P2 dust mask Safety glasses Steel cap boots Half-face respirator (P2 or P3 filters) Overalls Work gloves Cut-resistant gloves Hard hat	None required

5. PLANT AND EQUIPMENT

Plant / equipment	Licence or training needed	Inspection needed	Rego / ID	Last inspected	Certificate / report
Hand tools					
Power sander		Test and tag every 3 months on construction sites (AS/NZS 3012); visual check and RCD push-button test before use			

Plant / equipment	Licence or training needed	Inspection needed	Rego / ID	Last inspected	Certificate / report
Step ladder		Check before each use to the manufacturer and AS/NZS 1892; tag out damaged ladders			

6. CREW COMPETENCY, TICKETS AND LICENCES

Crew listed at sign-on below, with ticket and licence numbers.

7. EMERGENCY ARRANGEMENTS

Emergency number	000	**First aid kit**	In the work vehicle
Fire extinguisher	In the work vehicle	**Alarm and evacuation**	Shout for help and stop work. Make the area safe and go to the assembly point. Call the emergency number and send someone to meet the ambulance.
Reporting incidents	Notify the regulator immediately of any notifiable incident and preserve the site.		

8. IMPLEMENTING, MONITORING AND REVIEWING THE CONTROLS

How they are put in place	Controls are set up before the work starts. The person responsible explains this SWMS to every worker before they start, and workers sign to confirm they understand it.	**How they are monitored**	The person responsible checks the controls are in place before work starts each day and during the work, and talks to the workers about any problems. Stop work and review this SWMS if the work changes, the controls are not working, after any incident, or if a worker raises a concern.
When it is reviewed	Reviewed when the work or site changes, after any incident, if a control is not working, or if a worker or health and safety representative asks.		

Legal basis: Work Health and Safety Regulations 2011, Part 6.3 (Victoria: OHS Regulations 2017). A SWMS must be prepared before any high risk construction work starts. It must list the high risk work, the hazards and risks, the control measures, and how those controls will be put in place, monitored and reviewed. It must be easy for the workers to read and understand.

Keep this SWMS, and every revised version, until the high risk construction work is finished, where workers and inspectors can see it on site. If a notifiable incident happens during the work, keep it for at least 2 years after the incident.

9. REVIEW AND AMENDMENT RECORD

Rev	Date	By	What changed
1	9 Nov 2026		First issue

10. SIGN-OFF

	Name	Signature	Date	
Prepared by				
Person responsible (supervisor)				
Principal contractor review				Accepted for use: Yes / No

By signing below, each worker confirms they were consulted on and have read and understood this SWMS, and will follow it. If the work cannot be done as this SWMS says, stop as soon as it is safe and do not restart until the SWMS is reviewed.

Name	Role / company	Tickets / licences	Inducted	Signature	Date

Name	Role / company	Tickets / licences	Inducted	Signature	Date